


otes:

Characteristics:

A. Material (材料)

- 1) Housing: High Plastic Black (UL94V-0)
- 2) Pin C6801
- 3) Magnet: N52

B. Plating (电镀)

- 1) Plunger: Plating Min. 3u' Au over Min. 50u' Ni.

C. Electrical (电器性能)

- 1) Operating voltage: 12V Max.
- 2) Operating current: 2A Max.
- 3) Contact resistance: 30mohm Max.
at working height (Quiescence).

- 1) Don't exceed the Max. allowed compression

E. Environmental (工作环境)

- 1) Storage and operating temperature range:
-40°C ~ +85°C
- 2) Humidity range: 10% RH to 90% RH
- 3) Salt spray: 48H

F. Others (其它)

- 1) The dimensions marked * are critical,
Should be checked in production
- 2) RoHS compliant product.



深圳永探电子有限公司

UNLESS OTHERWISE SPECIFIED TOLERANCES ARE X.X ±0.10 X.XX ±0.05 X.XXX ANG. ±2°	APPROVED BY		DATE		TITLE 7P-2. 54PH磁吸-母座			
	CHECKED BY		DATE					
	DRAWN BY		DATE		DOCUMENT NO		PAGE	
	CXS		2024.11.19		DN011-003		1	
UNIT		SIZE	PART NO			REV	SHEET	SCALE
mm			*	A1	1/1	1:1		
		A4						