


otes:

Characteristics:

A. Material (材料)

- 1) Housing:High Plastic Black (UL94V-0)
- 2) Plunger:brass C6801
- 3) Barrel:brass C6801

B. Plating (电镀)

- 1) Plunger:Plating Min. 3u' Au over Min. 50u' Ni.

C. Electrical (电器性能)

- 1) Operating voltage: 12V Max.
- 2) Operating current: 2A Max.
- 3) Contact resistance: 30mohm Max.
at working height(Quiescence).


E. Environmental (工作环境)

- 1) Storage and operating temperature range:
-40°C~+85°C

- 2) Humidity range: 10% RH to 90% RH
- 3) Salt spray: 48H

F. Others (其它)

- 1) The dimensions marked * are critical, Should be checked in production
- 2) RoHS compliant product.



深圳永探电子有限公司

UNLESS OTHERWISE SPECIFIED		APPROVED BY		DATE		TITLE	
TOLERANCES ARE		CHECKED BY		DATE		7P-2.54PH磁吸-公座	
X.X							
±0.10							
X.XX		DRAWN BY		DATE		DOCUMENT NO	
±0.05						DN011-003	
X.XXX						PAGE	
ANG.						1	
±2							
UNIT	SIZE	PART NO	REV	SHEET	SCALE		
mm	A4	*	A1	1/1	1:1		
SER		DESCRIPTION		CHK		DATE	